



## H1080

Projektor pro domácí kino

### Optimální řešení domácího kina

Vivitek H1080 nabízí vysoký výkon a kvalitu obrazu pro využití pro domácí kino. Full HD rozlišení, vysoký kontrastní poměr, DLP® DarkChip2™, BrilliantColor™ a nízká hlučnost dělají z Vivitek H1080 optimálního společníka pro projekci filmů ve vysokém rozlišení.

#### Vlastnosti:

Rozlišení Full HD 1920 x 1080

Světelný výkon 1800 ANSI Lm,  
kontrastní poměr 5000:1

Velmi tichý provoz (26db)

2 x vstup HDMI v1.3

12V trigger výstup pro synchronní ovládání  
externích zařízení

DLP® DarkChip2™ and BrilliantColor™ technologie  
od Texas Instruments

Možnost uzamčení ovládacího panelu  
brání nechtěné změně nastavení

Kryt lampy na vrchní straně projektoru  
pro snadný přístup

Specifications	
Brightness	1800 Lumens (Typical)
Native Resolution	1080p (1920 x 1080)
Contrast Ratio	5000:1 (Full On/Off)
Lamp Life and Type	≈3000/2000 Hours (Standard/Boost Mode), 230W UHP
Lamp Part #	5811116206-SU
Display Type	Single 0.65" DarkChip2™ DLP® Technology by Texas Instruments
Throw Ratio	1.6 to 1.92:1 (Distance/Width)
Image Size (Diagonal)	25" to 300" (0.6 to 7.6 m)
Projection Distance	3.3' to 32.8' (1.0 to 10.0 m)
Projection Lens	F=2.55-2.72, f=21.3-24.5mm
Zoom Ratio	1.2:1 Manual Zoom/Focus
Aspect Ratio	16:9 Native, 4:3 Compatible
Offset	130%
Keystone Correction	±30° Vertical, Auto Keystone
Color Spectrum	1.07 Billion
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Speaker	5W Mono
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	1080p, UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, L)
I/O Connection Ports	HDMI v1.3 (x2), VGA-In, Component Video, Composite Video, S-Video, RCA Audio-In, Mini-Jack Audio-In, Mini-Jack Audio-Out, USB (Service), RS-232c, 12V Trigger
Security	Kensington® Lock Port, Security Bar
Weight	7.8 lbs (3.5 kg)
Dimensions (W x H x D)	13.2" x 4" x 10" (335 x 102 x 254 mm)
Noise Level	26dB/30dB (Standard/Boost Mode)
Power	Supply: AC Input 100 - 240V Consumption: 240 Watts (Standard Mode), 290 Watts (Boost Mode), <1 Watts (Standby Mode)
Operating Temperature	41 to 104°F (5 to 40°C), 80% Max Humidity
Warranty	1-Year Limited Warranty, 90-Day Lamp Warranty
Standard Accessories	AC Power Cord, Component Cable, Remote Control, Batteries for Remote, Lens Cap, User's Manual (CD), Warranty Card
Optional Accessories	Replacement Lamp, Remote
UPC	8 14964 33468 8

